



Cush-A-Nator® High Intensity Temp (HIT) has service temperatures of -65°F to 400°F (-53°C to 204°C).

Cush-A-Nator® High IntensityTemp (HIT) Tube Part No.			O.D. Tube Size	Dimensions (Inches)			
Steel	SS304	SS316		A	B	C	D
HT04	HT04SS	HT04S6	1/4"	0.25" (6mm)	0.62" (16mm)	0.27" (7mm)	0.98" (25mm)
HT06	HT06SS	HT06S6	3/8"	0.37" (9mm)	0.82" (21mm)	0.33" (8mm)	1.13" (29mm)
HT08	HT08SS	HT08S6	1/2"	0.50" (13mm)	0.94" (24mm)	0.40" (10mm)	1.34" (34mm)
HT10	HT10SS	HT10S6	5/8"	0.62" (16mm)	1.06" (27mm)	0.46" (12mm)	1.54" (39mm)
HT12	HT12SS	HT12S6	3/4"	0.75" (19mm)	1.20" (30mm)	0.52" (13mm)	1.68" (43mm)
HT14	HT14SS	HT14S6	7/8"	0.87" (22mm)	1.31" (33mm)	0.58" (15mm)	1.82" (46mm)
HT16	HT16SS	HT16S6	1"	1.00" (25mm)	1.44" (37mm)	0.65" (17mm)	1.95" (50mm)
HT18	HT18SS	HT18S6	1-1/8"	1.12" (28mm)	1.57" (40mm)	0.70" (18mm)	2.08" (53mm)
HT20	HT20SS	HT20S6	1-1/4"	1.25" (32mm)	1.70" (43mm)	0.77" (20mm)	2.21" (56mm)
HT32M	HT32MSS	HT32MS6	32mm	32mm	1.51" (38mm)	0.76" (19mm)	2.55" (65mm)
HT22	HT22SS	HT22S6	1-3/8"	1.37" (35mm)	1.82" (46mm)	0.83" (21mm)	2.34" (59mm)
HT24	HT24SS	HT24S6	1-1/2"	1.50" (38mm)	1.95" (50mm)	0.90" (23mm)	2.47" (63mm)
HT26	HT26SS	HT26S6	1-5/8"	1.62" (41mm)	2.07" (53mm)	0.96" (24mm)	2.60" (66mm)
HT28	HT28SS	HT28S6	1-3/4"	1.75" (45mm)	2.20" (56mm)	1.02" (26mm)	2.73" (69mm)
HT30	HT30SS	HT30S6	1-7/8"	1.87" (48mm)	2.32" (59mm)	1.09" (28mm)	2.86" (73mm)
HT32	HT32SS	HT32S6	2"	2.00" (51mm)	2.45" (62mm)	1.15" (29mm)	3.04" (77mm)
HT34	HT34SS	HT34S6	2-1/8"	2.12" (54mm)	2.57" (65mm)	1.27" (32mm)	3.23" (82mm)

HT36	HT36SS	HT36S6	2-1/4"	2.25" (57mm)	2.82" (72mm)	1.41" (36mm)	3.67" (93mm)
HT38	HT38SS	HT38S6	2-3/8"	2.37" (60mm)	2.82" (72mm)	1.41" (36mm)	3.67" (93mm)
HT40	HT40SS	HT40S6	2-1/2"	2.50" (64mm)	2.94" (75mm)	1.46" (37mm)	3.79" (96mm)
HT42	HT42SS	HT42S6	2-5/8"	2.62" (66mm)	3.07" (78mm)	1.53" (39mm)	3.92" (100mm)
HT46	HT46SS	HT46S6	2-7/8"	2.87" (73mm)	3.32" (84mm)	1.66" (42mm)	4.17" (106mm)
HT75M	HT75MSS	HT75MS6	75mm	75mm	3.37" (86mm)	1.69" (43mm)	4.68" (119mm)
HT48	HT48SS	HT48S6	3"	3.00" (76mm)	3.57" (91mm)	1.78" (45mm)	4.42" (112mm)
HT50	HT50SS	HT50S6	3-1/8"	3.12" (79mm)	3.57" (91mm)	1.78" (45mm)	4.42" (112mm)
HT56	HT56SS	HT56S6	3-1/2"	3.50" (89mm)	3.95" (100mm)	1.97" (50mm)	4.79" (122mm)
HT90M	HT90MSS	HT90MS6	90mm	90mm	3.86" (98mm)	1.94" (49mm)	5.23" (133mm)
HT64	HT64SS	HT64S6	4"	4.00" (102mm)	4.45" (113mm)	2.28" (58mm)	5.11" (130mm)
HT66	HT66SS	HT66S6	4-1/8"	4.12" (105mm)	4.57" (116mm)	2.34" (59mm)	5.54" (141mm)
HT110M	HT110MSS	HT110MS6	110mm	110mm	4.99" (127mm)	2.81" (71mm)	6.38" (162mm)
HT72	HT72SS	HT72S6	4-1/2"	4.50" (114mm)	4.95" (126mm)	2.53" (64mm)	5.92" (150mm)
HT125M	HT125MSS	HT125MS6	125mm	125mm	5.61" (142mm)	2.81" (71mm)	7.00" (178mm)
HT96	HT96SS	HT96S6	6"	6.00" (152mm)	6.62" (168mm)	3.31" (84mm)	7.63" (194mm)
HT160M	HT160MSS	HT160MS6	160mm	160mm	6.62" (168mm)	3.31" (84mm)	7.63" (194mm)
<b>Cush-A-Nator® High Intensity Temp (HIT) Tube Part No.</b>			<b>Pipe Size</b>	<b>Dimensions (Inches)</b>			
<b>Steel</b>	<b>SS304</b>	<b>SS316</b>		<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>
HT14P	HT14PSS	HT14PS6	1/2"	0.84" (21mm)	1.29" (33mm)	0.58" (15mm)	1.82" (46mm)
HT17P	HT17PSS	HT17PS6	3/4"	1.05" (27mm)	1.57" (40mm)	0.70" (18mm)	2.08" (53mm)
HT21P	HT21PSS	HT21PS6	1"	1.315" (33mm)	1.76" (45mm)	0.81" (21mm)	2.34" (59mm)
HT30P	HT30PSS	HT30PS6	1-1/2"	1.9" (48mm)	2.32" (59mm)	1.09" (28mm)	2.86" (73mm)
HT38P	HT38PSS	HT38PS6	2"	2.375" (60mm)	2.82" (72mm)	1.41" (36mm)	3.67" (93mm)
HT46P	HT46PSS	HT46PS6	2-1/2"	2.875" (73mm)	3.32" (84mm)	1.66" (42mm)	4.17" (106mm)
HT56P	HT56PSS	HT56PS6	3"	3.5" (89mm)	3.95" (100mm)	1.97" (50mm)	4.79" (122mm)
HT64P	HT64PSS	HT64PS6	3-1/2"	4" (102mm)	4.45" (113mm)	2.28" (58mm)	5.11" (130mm)
HT72P	HT72PSS	HT72PS6	4"	4.5" (114mm)	4.95" (126mm)	2.53" (64mm)	5.92" (150mm)